



### 2in1 Battery Hydraulic Crimping & Cutting Tools

Model	EZ-300/45	EZ-400/55
Power Input	18V 4.0Ah Li-ion Battery	18V 4.0Ah Li-ion Battery
Output	6 Ton	12 Ton
Stroke	17 mm	38 mm
Battery Capacity	320 Crimping per Cycle	320 Crimping per Cycle
	90 Cutting per Cycle	90 Cutting per Cycle
Charging Time	2 Hours	2 Hours
Crimping Range	16-300 mm <sup>2</sup>	16-400 mm <sup>2</sup>
Cutting Range	Ø45mm Aluminum, Copper, Armored Cable	Ø55mm Aluminum, Copper, Armored Cable
Accessories	2 pcs of Battery	2 pcs of Battery
	1 pcs of Battery Charger	1 pcs of Battery Charger
	1 Set of Shoulder Strap	1 Set of Shoulder Strap
	1 Set Crimping Head	1 pcs Machine Handle
	1 Set Cutting Head	1 Set Crimping Head
		1 Set Cutting Head
Crimping Dies	16,25,35,50,70,95,120,150	16,25,35,50,70,95,120,150,
	185,240,300 mm	185,240,300,400 mm
Packing Weight	21 kg	21 kg
Packing Dimension	600x170x530 mm	600x170x530 mm





## EZ-300 Electro-hydraulic pliers



<b>Contribute/ Trip</b>	60KN/17mm	<b>Crimp range</b>	Cu300mm <sup>2</sup> /Al240mm <sup>2</sup>
<b>Net weight</b>	4.6KG	<b>Battery capacity</b>	DC18V/5.0AH Li battery
<b>Pressure times</b>	320 times voltage per saturation(Cu cable 150mm <sup>2</sup> )		
<b>Mould configuration</b>	10、16、25、35、50、70、95、120、150、185、240、300mm <sup>2</sup>		



## EZ-400

### Electro-hydraulic pliers



Contribute/ Trip	120KN/42mm	Crimp range	Cu400mm <sup>2</sup> /Al300mm <sup>2</sup>
Net weight	7.5KG	Battery capacity	DC18V/5.0AH Li battery
Pressure times	320 times voltage per saturation(Cu cable 150mm <sup>2</sup> )		
Mould configuration	10/16/25/35/50/70/95/120/150/185/240/300/400 mm <sup>2</sup>		



### Battery Hydraulic Crimping Tools

Model	EB-630
Power Input	18V 4.0Ah Li-ion Battery
Output	20 Ton / 200 KN
Stroke	20 mm
Battery Capacity	120 Crimping per Cycle (Cu 150mm <sup>2</sup> )
Crimping Speed	6-18s
Charging Time	1 Hour
Crimping Range	Cu 25-630 mm <sup>2</sup> Al 15-500 mm <sup>2</sup>
Accessories	2 pcs of Battery 1 pcs of Battery Charger 1 Set of Shoulder Strap
Crimping Dies	25,35,50,70,95,120,150, 185,240,300,400,500,630 mm
Packing Weight	25 kg
Packing Dimension	650x170x490 mm