



Battery Powered Universal Tool, HHYD-60H



One head for crimping, cutting and punching - one tool for all Lightweight and well-balanced. Interchangeable crimping dies, cutting blades and punching adapter.

Only seconds of time is needed to switch crimping, cutting and punching functions.









Cut Cu/Al wire or armoured cable up to Φ 40mm



Punch holesΦ 22-Φ60mm



- •One universal head to complete crimping, cutting and punching jobs.
- •Two-stage hydraulic system features fast feed and power stroke upon reaching counter pressure, saving time.
- •10000+ cycle service life.
- •Ram retracts to original position automatically when operation is complete.
- •Manual retraction in case of need.
- •Audible buzzer and red LED light in case of error.
- •Quick motor stop for higher user safety.
- •Powerful 18V Li-ion battery with low battery warning.
- Ergonomic 2-component grip area and balanced center of gravity.
- •Sturdy plastic storage box.



Model	HHYD-60H
Hydraulic Ram Output	6.5 Ton
Ram stroke	42mm
Battery capacity	90 cutting cycles 320 crimping cycles 100 punching cycles
Cutting range	Ø40mm(Cu/Al and armoured cable)
Crimping range	16-300 mm ²
Punching range	Ø22-Ø60mm
Battery	18V/4.0Ah Li-ion
Charging time	2 hours
	ACCESSORIES
Crimping dies	16,25,35,50,70,95,120,150,185,240, 300 mm ²
Punching dies	22,27,34,43,49,60 mm
Qty of battery	2 pcs
Charger	1 pc
Blade	1 set
Adapter for crimping	1 pc
Adapter for punching	1 pc
Draw stud M20 \times 1.5	1 pc
Draw stud M10×1	1 pc
Spacer	1 pc
Seals	1set
Weight(Kg)	21.4
Packing size(mm)	585×500×170



Battery Powered Hydraulic Crimping Tool, HHYD-400E

- C-head with large 42 mm opening width
- Balanced centre of gravity for easy handling
- Very large crimping range up to 400 mm²
- Wide crimping

Open C-crimping head with 42 mm width, rotating 330°

- •Open C-crimping head with 42 mm width, rotating 330°.
- •Two-stage hydraulic system features fast feed and power stroke upon reaching counter pressure, saving time.
- 10000+ cycle service life.
- •Ram retracts to original position automatically when operation is complete.
- •Manual retraction in case of need.
- Audible buzzer and red LED light in case of error.
- •Quick motor stop for higher user safety.
- Powerful 18V Li-ion battery with low battery warning.
- Ergonomic 2-component grip area and balanced center of gravity.
- Sturdy plastic storage box.





Model	HHYD-400E
Hydraulic Ram Output	11 Ton
Ram Stroke	42 mm
Battery capacity	150 crimping cycles
Crimping range	16-400 mm²
Crimping times	6s-18s(Depend on the size of cable)
Battery	18V/4.0Ah Li-ion
Charging time	2 hours
	ACCESSORIES
Crimping dies	16,25,35,50,70,95,120,150,185,240, 300,400 mm ²
Qty of battery	2 pcs
Charger	1 pc
Seals	1set
Weight(Kg)	17.3
Packing size(mm)	585×500×170







Battery Powered Hydraulic Crimping Tool, HHYD-400D





Characteristics:

- •Open C-crimping head, rotating 330°.
- •Two-stage hydraulic system features fast feed and power stroke upon reaching counter pressure, saving time.
- •10000+ cycle service life.
- •Ram retracts to original position automatically when operation is complete.
- •Manual retraction in case of need.
- Audible buzzer and red LED light in case of error.
- •Quick motor stop for higher user safety.
- Powerful 18V Li-ion battery with low battery warning.
- Ergonomic 2-component grip area and balanced center of gravity.
- •Sturdy plastic storage box.

Model	Hydraulic Ram Output	Ram stroke	Battery capacity	Crimping range	Crimping times	Battery	Crimping dies	Weight (Kg)	Packing size(mm)
HHYD-400D	11 Ton	32 mm	180 crimping cycles	16-400 mm²	5s-15s (Depend on the size of cable)	18V/4.0 Ah Li-ion	16,25,35,50,70,95, 120,150,185,240, 300,400 mm ²	16.6	585×500× 170

Battery Powered Hydraulic Crimping Tool, HHYD-400U





- •H-head for deep groove, rotating 350°.
- •Two-stage hydraulic system features fast feed and power stroke upon reaching counter pressure, saving time.
- •10000+ cycle service life.
- •Ram retracts to original position automatically when operation is complete.
- •Manual retraction in case of need.
- •Audible buzzer and red LED light in case of error.
- •Quick motor stop for higher user safety.
- •Powerful 18V Li-ion battery with low battery warning.
- •Ergonomic 2-component grip area and balanced center of gravity.
- •Sturdy plastic storage box.

Model	Hydraulic Ram Output	Ram stroke	Battery capacity	Crimping range	Crimping times	Battery	Crimping dies	Weight (Kg)	Packing size(mm)
HHYD-400U	11 Ton	20 mm	180 crimping cycles	16-400 mm²	4s-12s (Depend on the size of cable)	18V/4.0 Ah Li-ion	16,25,35,50,70,95, 120,150,185,240, 300,400 mm ²	16.1	585×500× 170





Battery Powered Hydraulic Crimping Tool, HHYD-300H



Characteristics:

- •Flip-top head enables quick change of crimping dies.
- •Two-stage hydraulic system features fast feed and power stroke upon reaching counter pressure, saving time.
- •10000+ cycle service life.
- •Ram retracts to original position automatically when operation is complete.
- •Manual retraction in case of need.
- •Audible buzzer and red LED light in case of error
- Quick motor stop for higher user safety.
- Powerful 18V Li-ion battery with low battery warning.
- Ergonomic 2-component grip area and balanced center of gravity.
- •Sturdy plastic storage box.

Model	Hydraulic Ram Output	Ram stroke	Battery capacity	Crimping range	Crimping times	Battery	Crimping dies	Weight (Kg)	Packing size(mm)
HHYD-300H	6.5 Ton	18 mm	320 crimping cycles	16-300 mm²	3s-6s (Depend on the size of cable)	18V/4.0 Ah Li-ion	16,25,35,50,70,95, 120,150,185,240, 300 mm ²	14.4	585×500× 170

Battery Powered Hydraulic Crimping Tool, HHYD-300G





- •Flip-top head enables quick change of crimping dies.
- •Two-stage hydraulic system features fast feed and power stroke upon reaching counter pressure, saving time.
- •10000+ cycle service life.
- •Ram retracts to original position automatically when operation is complete.
- •Manual retraction in case of need.
- •Audible buzzer and red LED light in case of error.
- •Quick motor stop for higher user safety.
- •Powerful 18V Li-ion battery with low battery warning.
- •Ergonomic 2-component grip area and balanced center of gravity.
- •Sturdy plastic storage box.

Model	Hydraulic Ram Output	Ram stroke	Battery capacity	Crimping range	Crimping times	Battery	Crimping dies	Weight (Kg)	Packing size(mm)
HHYD-300G	6.5 Ton	15 mm	320 crimping cycles	16-300 mm²	3s-6s (Depend on the size of cable)	18V/4.0 Ah Li-ion	16,25,35,50,70,95, 120,150,185,240, 300 mm ²	13.7	585×500× 170







Hand Operated Hydraulic Universal Tool, HHY-60H



Aluminum pump lever and housing result in low weight. One universal head for crimping, cutting and punching.

Built-in safety valve

- •Universal head, flip-top style, rotatable.
- •Light weight due to high quality aluminum housing.
- •Thanks to the automatic retraction function, poor crimps are avoided, more safety and shorter intervals between crimping operations.
- Manual release in case of need.
- •The rotatable head permits to work in tight locations.
- Faster operation with less force thanks to the 2-stage hydraulic system
- •Closed work head, flip top style, rotatable.
- •Sturdy steel storage box.





Crimp copper lug 16-300mm² or aluminum lug 10-240mm²



Cut Cu/Al wire or armoured cable up to Φ 40mm



Punch holesΦ 22-Φ60mm





Model	HHY-60H
Hydraulic Ram Output	6.5 Ton
Ram Stroke	42 mm
Cutting range(mm)	Ø40(Cu/Al and armoured cable)
Crimping range(mm²)	16-300
Punching range(mm)	Ø22.5-Ø61.5
G.W.(kg)	14.5
Packing size(mm)	610×210×110
	Accessories
Crimping dles(mm²)	16,25,35,50,70,95,120,150,185,240, 300
Punching dles(mm)	22,27,34,43,49,60
Blades	1 set
Crimping adapter	1 pc
Punching adapter	1 pc
Draw stud M20x1.5	1 pc
Draw stud M10 x 1	1 pc
Spacer	1 pc
Sealing ring of cylinder	1 set
Sealing ring of safety valve	1 set





Hand Operated Hydraulic Crimping Tool, HHY-400E

Aluminum pump lever and housing result in low weight

C-head with large 42 mm opening width Very large crimping range up to 400 mm² Wide crimping





Characteristics:

- •Open C crimping head with 42 mm width, rotatable.
- •Large crimping area up to 400mm².
- •Light weight due to high quality aluminum housing.
- •Thanks to the automatic retraction function, poor crimps are avoided, more safety and shorter intervals between crimping operations.
- •Manual release in case of need.
- •The rotatable head permits to work in tight locations.
- Faster operation with less force thanks to the 2-stage hydraulic system.
- •Sturdy steel storage box.





Model	HHY-400E
Hydraulic Ram Output	11 Ton
Ram Stroke	42 mm
Crimping range(mm²)	16-400
Crimp pattern	Hexagonal type
Crimping dies(mm²)	50,70,95,120,150,185,240,300,400
G.W.(kg)	12.1
Packing size(mm)	610X210X110

Hand Operated Hydraulic Crimping Tool, HHY-400D

Aluminum pump lever and housing result in low weight Open C head, large crimping area up to 400mm²

Built-in safety valve





- \bullet Open C crimping head, rotatable, large crimping area up to 400mm².
- •Light weight due to high quality aluminum housing.
- •Thanks to the automatic retraction function, poor crimps are avoided, more safety and shorter intervals between crimping operations.
- •Manual release in case of need.
- •The rotatable head permits to work in tight locations.
- Faster operation with less force thanks to the 2-stage hydraulic system.
- •Sturdy steel storage box.





Model	HHY-400D
Hydraulic Ram Output	11 Ton
Ram Stroke	32 mm
Crimping range(mm ²)	16-400
Crimp pattern	Hexagonal type
Crimping dies(mm²)	50,70,95,120,150,185,240,300,400
G.W.(kg)	11.9
Packing size(mm)	610X210X110





Hand Operated Hydraulic Crimping Tool, HHY-400U

Aluminum pump lever and housing result in low weight

Built-in safety valve





Characteristics

- •H-head for deep groove applications.
- •Large crimping area up to 400mm².
- •Light weight due to high quality aluminum housing.
- •Thanks to the automatic retraction function, poor crimps are avoided, more safety and shorter intervals between crimping operations.
- •Manual release in case of need.
- •The rotatable head permits to work in tight locations.
- Faster operation with less force thanks to the 2-stage hydraulic system.
- •Sturdy steel storage box.





Model	HHY-400U
Hydraulic Ram Output	11 Ton
Ram Stroke	20 mm
Crimping range(mm ²)	16-400
Crimp pattern	Hexagonal type
Crimping dies(mm²)	50,70,95,120,150,185,240,300,400
G.W.(kg)	9.3
Packing size(mm)	610X210X110

Hand Operated Hydraulic Crimping Tool, HHY-300G

Aluminum pump lever and housing result in low weight.

Extremely easy to handle, even with frequent operations in tight locations





- •Compact flip-top crimping head, rotatable.
- •Light weight due to high quality aluminum housing.
- •Thanks to the automatic retraction function, poor crimps are avoided, more safety and shorter intervals between crimping operations.
- Manual release in case of need.
- •The rotatable head permits to work in tight locations.
- Faster operation with less force thanks to the 2-stage hydraulic system.
- •Sturdy steel storage box.







Model	HHY-300G
Hydraulic Ram Output	6.5 Ton
Ram Stroke	17 mm
Crimping range(mm ²)	16-300
Crimp pattern	Hexagonal type
Crimping dies(mm²)	16,25,35,50,70,95,120,150,185,240, 300
G.W.(kg)	9
Packing size(mm)	610X210X110



Hand Operated Hydraulic Crimping Tools

HHY-400 Built-in safety valve



Characteristics:

- •Compact design, rugged and durable.
- •Rotatable C crimping head.
- •Built-in pressure relief valve for overload protection.
- •Two-speed pump to reduce cycle time.
- •Ram retraction by turning the release knob anticlockwise.
- •Sturdy steel storage box.

Model	HHY-400
Hydraulic Ram Output	11 Ton
Ram Stroke	30 mm
Crimping range(mm ²)	16-400
Crimp pattern	Hexagonal type
Crimping dies(mm²)	50,70,95,120,150,185,240,300,400
G.W.(kg)	10
Packing size(mm)	560X130X140

HHY-400B Built-in safety valve



Characteristics:

- •Compact design, rugged and durable.
- Rotatable C crimping head.
- •Built-in pressure relief valve for overload protection
- •Two-speed pump to reduce cycle time.
- •Ram retraction by turning the release knob anticlockwise.
- •Molded plastic carry case.

Model	HHY-400B
Hydraulic Ram Output	11 Ton
Ram Stroke	32 mm
Crimping range(mm ²)	16-400
Crimp pattern	Hexagonal type
Crimping dies(mm²)	50,70,95,120,150,185,240,300,400
G.W.(kg)	11.5
Packing size(mm)	770X135X240

HHY-400C Built-in safety valve



- •Compact design, rugged and durable.
- •Rotatable C crimping head.
- •Built-in pressure relief valve for overload protection
- •Two-speed pump to reduce cycle time.
- \bullet Ram retraction by turning the release knob anticlockwise.
- Molded plastic carry case.

Model	HHY-400C
Hydraulic Ram Output	11 Ton
Ram Stroke	32 mm
Crimping range(mm²)	16-400
Crimp pattern	Hexagonal type
Crimping dies(mm²)	50,70,95,120,150,185,240,300,400
G.W.(kg)	11.3
Packing size(mm)	770X230X130







Hand Operated Hydraulic Crimping Tools

HHY-300D Built-in safety valve



Characteristics:

- •Compact design, rugged and durable.
- •Rotatable flip top crimping head.
- •Built-in pressure relief valve for overload protection
- •Two-speed pump to reduce cycle time.
- •Ram retraction by turning the release knob anticlockwise.
- •Molded plastic carry case.

Model	HHY-300D
Hydraulic Ram Output	8 Ton
Ram Stroke	13 mm
Crimping range(mm ²)	16-300
Crimp pattern	Hexagonal type
Crimping dies(mm²)	16,25,35,50,70,95,120,150,185,240, 300
G.W.(kg)	7.7
Packing size(mm)	540X240X140

HHY-300B Built-in safety valve



Characteristics:

- •Compact design, rugged and durable.
- •Rotatable H crimping head.
- •Built-in pressure relief valve for overload protection
- •Two-speed pump to reduce cycle time.
- •Ram retraction by turning the release knob anticlockwise.
- Molded plastic carry case.

Model	HHY-300B
Hydraulic Ram Output	11 Ton
Ram Stroke	18 mm
Crimping range(mm ²)	16-300
Crimp pattern	Hexagonal type
Crimping dies(mm²)	16,25,35,50,70,95,120,150,185,240, 300
G.W.(kg)	8.4
Packing size(mm)	540X120X240

HHY-300 Built-in safety valve



- •Compact design, rugged and durable.
- •Rotatable C crimping head.
- •Built-in pressure relief valve for overload protection
- •Two-speed pump to reduce cycle time.
- •Ram retraction by turning the release knob anticlockwise.
- Molded plastic carry case.

Model	HHY-300
Hydraulic Ram Output	11 Ton
Ram Stroke	17 mm
Crimping range(mm ²)	16-300
Crimp pattern	Hexagonal type
Crimping dies(mm²)	16,25,35,50,70,95,120,150,185,240, 300
G.W.(kg)	9.5
Packing size(mm)	540X120X240





Hand Operated Hydraulic Crimping Tools

HHY-300C Built-in safety valve



Characteristics:

- •Compact design, rugged and durable.
- •Rotatable C crimping head.
- •Built-in pressure relief valve for overload protection.
- •Two-speed pump to reduce cycle time.
- •Ram retraction by turning the release knob anticlockwise.
- Molded plastic carry case.

Model	HHY-300C
Hydraulic Ram Output	11 Ton
Ram Stroke	26 mm
Crimping range(mm²)	16-300
Crimp pattern	Hexagonal type
Crimping dies(mm²)	16,25,35,50,70,95,120,150,185,240, 300
G.W.(kg)	11
Packing size(mm)	770X240X130

HHY-300E

Built-in safety valve



Characteristics:

- •Compact design, rugged and durable.
- •Rotatable H crimping head.
- •Built-in pressure relief valve for overload protection.
- •Two-speed pump to reduce cycle time.
- •Ram retraction by turning the release knob anticlockwise.
- •Molded plastic carry case.

Model	HHY-300E
Hydraulic Ram Output	11 Ton
Ram Stroke	22 mm
Crimping range(mm ²)	16-300
Crimp pattern	Hexagonal type
Crimping dies(mm²)	16,25,35,50,70,95,120,150,185,240, 300
G.W.(kg)	7.4
Packing size(mm)	540X120X240

HHY-300A



- •Rugged, durable and affordable crimping tool.
- Molded plastic carry case.

Model	HHY-300A
Hydraulic Ram Output	9 Ton
Ram Stroke	18 mm
Crimping range(mm ²)	10-300
Crimp pattern	Hexagonal type
Crimping dies(mm²)	16,25,35,50,70,95,120,150,185,240, 300
G.W.(kg)	6.4
Packing size(mm)	533X206X102





ELECTRICAL INSTALLATION TOOLS CRIMPING



Hand Operated Hydraulic Crimping Tools

HHY-400A



Characteristics:

- Rugged, durable and affordable crimping tool.
- Molded plastic carry case.

Model	HHY-400A
iviouei	ППТ- 4 00А
Hydraulic Ram Output	14 Ton
Ram Stroke	16 mm
Crimping range(mm ²)	16-400
Crimp pattern	Hexagonal type
Crimping dies(mm²)	16,25,35,50,70,95,120,150,185,240, 300,400
G.W.(kg)	15
Packing size(mm)	625X110X240

HHY-240B



Characteristics:

- Rugged, durable and affordable crimping tool.Molded plastic carry case.

Model	HHY-240B
Hydraulic Ram Output	11 Ton
Ram Stroke	19 mm
Crimping range(mm²)	16-240
Crimp pattern	Hexagonal type
Crimping dies(mm²)	16,25,35,50,70,95,120,150,185,240
G.W.(kg)	9.3
Packing size(mm)	640X140X160

HHY-240C



- •Rugged, durable and affordable crimping tool.
- Molded plastic carry case.

Model	HHY-240C
Hydraulic Ram Output	10 Ton
Ram Stroke	15.5 mm
Crimping range(mm ²)	10-240
Crimp pattern	Hexagonal type
Crimping dies(mm²)	16,25,35,50,70,95,120,150,185,240
G.W.(kg)	6.3
Packing size(mm)	533X206X102





Hand Operated Hydraulic Crimping Tools

HHY-240A



Characteristics:

- •Rugged, durable and affordable crimping tool.
- •Comes in plastic carry case.

Model	HHY-240A
Hydraulic Ram Output	9 Ton
Ram Stroke	15.5 mm
Crimping range(mm ²)	10-240
Crimp pattern	Hexagonal type
Crimping dies(mm²)	16,25,35,50,70,95,120,150,185,240
G.W.(kg)	6.3
Packing size(mm)	533X206X102

HHY-120A



Characteristics:

- Rugged, durable and affordable crimping tool.
- •Comes in plastic carry case.

Model	HHY-120A
Hydraulic Ram Output	7 Ton
Ram Stroke	15.5 mm
Crimping range(mm ²)	10-120
Crimp pattern	Hexagonal type
Crimping dies(mm²)	10,16,25,35,50,70,95,120
G.W.(kg)	4.5
Packing size(mm)	430X190X90

HHY-70A



- $\bullet \mbox{Rugged},$ durable and affordable crimping tool.
- •Comes in plastic carry case.

Model	HHY-70A
Hydraulic Ram Output	5 Ton
Ram Stroke	10 mm
Crimping range(mm²)	6-70
Crimp pattern	Hexagonal type
Crimping dies(mm²)	6,10,16,25,35,50,70
G.W.(kg)	2.8
Packing size(mm)	355X173X83

