



MINI DIGITAL TORQUE WRENCH



230mm

1/4" 10N.m

Connector	1/4
Length	230 mm
Resolution	0.01N
Torque range 0.3~10Nm	
Accuracy	Clockwise: ±2% Counterclockwise: ±2.5%

Storage Box



230mm

1/4" 30N.m

Connector	1/4
Length	230 mm
Resolution	0.01N
Torque range 0.9~30Nm	
Accuracy	Clockwise: ±2% Counterclockwise: ±2.5%

Storage Box




240mm

3/8" 60N.m

Connector	3/8
Length	240 mm
Resolution	0.01N
Torque range 1.8~60Nm	
Accuracy	Clockwise: ±2% Counterclockwise: ±2.5%

Storage Box




285mm

1/2" 100N.m

Connector	1/2
Length	285 mm
Resolution	0.01N
Torque range 3~100Nm	
Accuracy	Clockwise: ±2% Counterclockwise: ±2.5%

Storage Box





1/4" DRIVE DIGITAL TORQUE WRENCH



390mm

1/4" Connector

Connector	1/4
Length	390 mm
Min.scale value	0.01
Size of replaceable head connection	9*12

Torque range 0.5~10 Nm

Storage Box



390mm

1/4" Connector

Connector	1/4
Length	390 mm
Min.scale value	0.01
Size of replaceable head connection	9*12

Torque range 1.5~30 Nm

Storage Box





3/8" DRIVE DIGITAL TORQUE WRENCH

420mm

3/8" Connector

Connector	3/8
Length	420 mm
Min.scale value	0.01
Size of replaceable head connection	9*12
Torque range 1.5~30 Nm	

Storage Box

420mm

3/8" Connector

Connector	3/8
Length	420 mm
Min.scale value	0.01
Size of replaceable head connection	9*12
Torque range 3~60 Nm	

Storage Box

420mm

3/8" Connector

Connector	3/8
Length	420 mm
Min.scale value	0.01
Size of replaceable head connection	9*12
Torque range 4.25~85 Nm	

Storage Box

420mm

3/8" Connector

Connector	3/8
Length	420 mm
Min.scale value	0.1
Size of replaceable head connection	9*12
Torque range 6.75~135Nm	

Storage Box



1/2" DRIVE DIGITAL TORQUE WRENCH



535mm



1/2" Connector

Connector	1/2
Length	535 mm
Min.scale value	0.1
Size of replaceable head connection	14*18
Torque range 6.75~135Nm	

Storage Box




535mm



1/2" Connector

Connector	1/2
Length	535 mm
Min.scale value	0.1
Size of replaceable head connection	14*18
Torque range 10~200Nm	

Storage Box




655mm



1/2" Connector

Connector	1/2
Length	655 mm
Min.scale value	0.1
Size of replaceable head connection	14*18
Torque range 17~340Nm	

Storage Box




655mm



1/2" 410N.m

Connector	1/2
Length	655 mm
Resolution	0.1N
Torque range 17~410Nm	
Accuracy	Clockwise: $\pm 2\%$ Counterclockwise: $\pm 2.5\%$

Storage Box



**3/4" DRIVE DIGITAL TORQUE WRENCH**

950mm



3/4" Connector

Connector	3/4
Length	950 mm

Min.scale value	0.1
-----------------	-----

Size of replaceable head connection

Torque range 25~500Nm

Storage Box



1220mm



3/4" Connector

Connector	3/4
Length	1220 mm

Min.scale value	0.1
-----------------	-----

Size of replaceable head connection

Torque range 42.5~850Nm

Storage Box

