



Couplers



The couplers are for quick connection of hose end to system components, working pressure 700 bar.

Thread sealer

To seal NPTF thread use one of the new anaerobic thread sealers or Teflon paste.

Picture		Part Number			Dimensions (mm)					Pressure rating
		Complete Set	Female Half	Male Half	A	B	C	D	E	
		HC7001	HC7001F	HC7001M	87	53	M10x1.5 female/ M16x1.5 male	27	22	700 bar
		HC7002	HC7002F	HC7002M	94	65	R2 3/8	30.3	27	700 bar
		HC7003	HC7003F	HC7003M	83.5	73.5	3/8" NPT	35	32	700 bar
		HC7004	HC7004F	HC7004M	83.5	73.5	3/8" NPT	35	32	700 bar
		HC7005	HC7005F	HC7005M	74.5	60.8	1/4" NPT	28.6	28	700 bar
		HC7006	HC7006F	HC7006M	61	44	1/4" NPT	25	22	700 bar
		HC7007	HC7007F	HC7007M	94	65	R2 3/8	30.3	27	700 bar
		HC7008	HC7008F	HC7008M	83	59	R2 3/8	30.3	27	700 bar
		HC15001	HC15001F	HC15001M	81	61.2	G1/4"	28	22	1500 bar

Note: Value A is total length when male and female half are connected.